



Perfect drying by convective flow of warm air



Hygienic cleansing by UV-C light for your health



Health improving blue light



Easy handling by simple touch on a single button



Mobility by USB-C standard



Automatic room- and temperature modulation



Automatic turn-off after comfort drying



All features controlled by microprocessor



Highest product quality with 2 year warranty



Energy-efficient, gentle and absolutely safe

PRODUCT DESCRIPTION

The DRY-SPACE UV® is an electronic drying appliance with universal USB-C plug and UV-C light for hygienic cleansing for nightly use at home, to store & care all types of Cochlear implants and Bone conduction devices. Also binaural implants are gently dried and cleansed hygienically.

IDENTIFICATION

Product name: DRY-SPACE UV®
REF: 80210101
WEEE-Reg. no.: DE 47525015

 flow-med GmbH
Weinbergweg 10
73773 Aichwald
Germany

TECHNICAL DATA

Drying: Drying temperature 45°C (113°F) +/- 3°C (37.4 °F) by thermal convection
Sensor button: 1x touch for 5 hours comfort drying
Touch for 3 seconds for manual switch-off (outside UV-C mode)
Switch-off: Automatic after 5 hours
Cleansing: 1 minute at start + 30 sec. at the end of drying with UV-C light with 253.7 nm wavelength
Up to 99.9% of all common germs and bacteria are effectively eliminated
UV-C intensity max. 4900 µW/cm², coverage area at 10 cm ~1.200 µW/cm²
Operation: 5V USB base via supplied USB switching power supply or USB 2.0 interface
Safety: Input voltage monitoring at < 4 V and > 6 V
Automatic safety shutdown at temperatures > 70°C (158°F)
Power consumption: Average power 6.8 W
Maximum power (UV-C) 8.8 W
Stand-by power < 0.1 W

PACKAGING CONTENT

DRY-SPACE UV®
USB universal power supply
Adapter EU / UK / SG / US / CA / JP / AUS
USB-C cable (USB-A to USB-C) 1.0 m
Instruction for use

ENERGY SUPPLY

Electronic USB universal switching power supply (class VI)
Input: 100-240 V, AC 50/60 Hz
Output: 5V, 2.5A, DC
Type: EU / UK / SG / US / CA / JP / AUS included

WARRANTY

2 Years from production date **LOT**

LABEL



DIMENSIONS, WEIGHT AND UDI-DI

Unit:	146 mm x 116 mm x 42 mm (L x W x H)	170 g	UDI-DI
1 Unit carton:	250 mm x 185 mm x 45 mm (L x W x H)	500 g	4260277012342
10 Unit carton:	380 mm x 260 mm x 230 mm (L x W x H)	5.250 g	4260277012359
20 Unit carton:	760 mm x 270 mm x 250 mm (L x W x H)	11.700 g	4260277012366