

Product Name: egger LP/H modelling paste (beige, Xpress)

REF: 31000, 31020

Date of print: 11.05.2021 Date of last alteration: 11.05.2021



Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

egger LP/H modelling paste (beige, Xpress)

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture

Ligth curing modelling paste for use in audiology.

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor: egger Otoplastik+Labortechnik GmbH

Street/POB-No.: Aybühlweg 59

Postal code/city/country: 87439 Kempten/Germany

Telephone: +49 831 58113-60 Telefax: +49 831 58113-14 Internet: www.egger.online E-mail: sales@egger.online

1.4. Emergency telephone number: +49 89 19240

Emergency number: Munich, Germany, toxicological dep. of the II. Med. Hospital)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Regulation (EC) No. 1272/2008

Hazard categories:

Respiratory or skin sensitisation: Skin Sens. 1B

Hazard Statements:

May cause an allergic skin reaction.

2.2. Label elements

Regulation (EC) No. 1272/2008 Hazard components for labelling

aliphatic urethane acrylate

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P302+P352 IF ON SKIN: Wash with plenty of water.



Product Name: egger LP/H modelling paste (beige, Xpress)

REF: 31000, 31020

Date of print: 11.05.2021 Date of last alteration: 11.05.2021



Page 2 of 10

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/ container in accordance with local and national regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of acrylic/methacrylic resins with auxilliary matters.

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	GHS Classification				
	aliphatic urethane acr	ylate		1 - < 5 %	
	906-949-5		01-2120266262-60		
	Skin Sens. 1B, Aquatic	Skin Sens. 1B, Aquatic Chronic 2; H317 H411			
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			< 1 %	
	278-355-8	015-203-00-X			
	Repr. 2, Skin Sens. 1B,	Aquatic Chronic 2; H361f	H317 H411		
21245-02-3	2-Ethylhexyl 4-(dimeth	2-Ethylhexyl 4-(dimethylamino)benzoate		< 1 %	
	244-289-3		01-2120766649-35		
	Repr. 1B; H360				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water.

Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).



Product Name: egger LP/H modelling paste (beige, Xpress)

REF: 31000, 31020

Date of print: 11.05.2021 Date of last alteration: 11.05.2021



Page 3 of 10

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.



Product Name: egger LP/H modelling paste (beige, Xpress)

REF: 31000, 31020

Date of print: 11.05.2021 Date of last alteration: 11.05.2021



Page 4 of 10

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs. Keep away from all kind of ligth. An inert gas blanket should not be applied, because the stability of the product depends on the presence of oxygen (air).

Hints on joint storage

Keep away from spontaneous flammable or combustible substances.

Further information on storage conditions

Keep away from all kind of ligth. An inert gas blanket should not be applied, because the stability of the product depends on the presence of oxygen (air).

7.3. Specific end use(s)

Ligth curing material for repair and modeling of earmoulds. For use by trained specialist staff.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber).

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Paste, low-viscosity

Colour: beige

Odour: faintly like esters



Product Name: egger LP/H modelling paste (beige, Xpress)

REF: 31000, 31020

Date of print: 11.05.2021 Date of last alteration: 11.05.2021



Page 5 of 10

		Test method
pH-Value:	not determined	
Changes in the physical state		
Melting point:	not determined	
Initial boiling point and boiling range:	not determined	
Flash point:	>100 °C	DIN 51755
Flammability		
Solid:	not applicable	
Gas:	not applicable	
Explosive properties	The product is not: Explosive.	
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Auto-ignition temperature		
Solid:	not applicable	
Gas:	not applicable	
Decomposition temperature:	>=190 °C	
Oxidizing properties	Not oxidizing.	
Vapour pressure (at 20 °C):	<1 hPa	
Density (at 20 °C):	1.25-1.35 g/cm³	DIN 51757
Water solubility:	insoluble	
Solubility in other solvents	not determined	
Partition coefficient:	not determined	
Vapour density:	not determined	
Evaporation rate:	not determined	

9.2. Other information

Solid content: not determined.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with: strong oxidising agents, strong alcaline or acidic materials.

10.4. Conditions to avoid

Ultra-violet ligth and dayligth initiate polymerisation of the product. Therefore keep only in tigthly closed containers away from any sources of ligth. Keep in a refrigerator at 2°C - 25°C / 36°F - 77 °F.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.



Product Name: egger LP/H modelling paste (beige, Xpress)

REF: 31000, 31020

Date of print: 11.05.2021 Date of last alteration: 11.05.2021



Page 6 of 10

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

For the product itself no toxicological data are available. In products with a comparable composition,

a LD50 (orally, species rat) of > 5000 mg/kg has been found.

CAS No	Chemical name	Chemical name			
	Exposure route	Dose	Species	Source	Method
	aliphatic uretha	aliphatic urethane acrylate			
	oral	oral LD50 >5000 mg/kg Rat OECD 401			
75980-60-8	diphenyl(2,4,6-t	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
21245-02-3	2-Ethylhexyl 4-(2-Ethylhexyl 4-(dimethylamino)benzoate			
	oral	LD50 14.900 mg/kg	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (aliphatic urethane acrylate; diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide).

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	aliphatic urethane acrylate					
	Acute algae toxicity	ErC >0.68 mg/l	72 h	(algae)	OECD 201	
	Acute crustacea toxicity	EC >1.2 mg/l	48 h	(daphnia)	OECD 202	



Product Name: egger LP/H modelling paste (beige, Xpress)

REF: 31000, 31020

Date of print: 11.05.2021 Date of last alteration: 11.05.2021



Page 7 of 10

75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	Acute algae toxicity	ErC >2.01 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 3.53 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	(>1000 mg/l)	3 h	Activated sludge		
21245-02-3	2-Ethylhexyl 4-(dimethylamino)benzoate					
	Acute fish toxicity	LC50 0.235 mg/l	96 h	QSAR		
	Acute algae toxicity	ErC50 <0.015	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 >0.031 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	(1000 mg/l)	3 h	Activated sludge		

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name	Chemical name				
	Method	Method Value d Source				
	Evaluation	Evaluation				
	aliphatic urethane	aliphatic urethane acrylate				
	OECD 301B	22 %	28			
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			•		
	0 - 10 %					
	Not readily biodegradable (according to OECD criteria).					

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	3.1

BCF

CAS No	Chemical name	BCF	Species	Source
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	47- 55	Cyprinus carpio (Common Carp)	

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Not identivied as PBT / vPvB substances.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.



Product Name: egger LP/H modelling paste (beige, Xpress)

REF: 31000, 31020

Date of print: 11.05.2021 Date of last alteration: 11.05.2021



Page 8 of 10

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

- **14.1. UN number:** No dangerous good in sense of this transport regulation.
- **14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
- 14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

- **14.1. UN number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
- **14.4. Packing group:** No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

- **14.1. UN number:** No dangerous good in sense of this transport regulation.
- 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
- 14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-IT/IATA-DGR)

- **14.1. UN number:** No dangerous good in sense of this transport regulation.
- **14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.
- 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
- 14.4. Packing group: No dangerous good in sense of this transport regulation.

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the

,juvenile work protection guideline (94/33/EC).



Product Name: egger LP/H modelling paste (beige, Xpress)

REF: 31000, 31020

Date of print: 11.05.2021 Date of last alteration: 11.05.2021



Page 9 of 10

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50 %

LD50: Lethal dose, 50 %

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50 % EL50: Effect loading, 50 %

EC50: Effective Concentration 50 %

ErC50: Effective Concentration 50 %, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation

intérieures)

EmS: Emergency Schedules MFAG: Medical First Aid Guide

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container SVHC: Substance of Very High Concern

@1602.B016012

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1B; H317	Calculation method



Product Name: egger LP/H modelling paste (beige, Xpress)

REF: 31000, 31020

Date of print: 11.05.2021 Date of last alteration: 11.05.2021



Page 10 of 10

Relevant H and EUH statements (number and full text)

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H361f Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)