

CALLING/TALKING (Base)

- Hearing Aid Compatible
- Adjustable receiving volume control (up to **30dB**)
- 4 one-touch memories, 3 with pictures
- Speaker phone
- Redial function for last 10 outgoing calls
- 50 phonebook memories
- Mute/Pause function
- Keyboard
 - Large keys (25x14mm)
 - Big characters (10mm)



BASE LCD DISPLAY

- Large screen
- White backlight
- Choice of 6 languages on the base (English, German, French, Italian, Spanish and Russian)
- Navigation menu
- Time stamping
- Alarm
- Key lock
- Talk time indication

ANSWERING MACHINE

- 15 minutes of recording time
- On/Off key
- 2 announcements (message record or no message record option)
- 2 answering machine modes
- Visual info. on the base about number of messages
- 4-digit user selectable remote codes
- Remote control for messages on handset
- Erase each/all messages
- Time & date stamp on recorded messages
- 3 languages (English, German and French)
- Voice memo recoder
- Choice of the number of ringtones before answering machine answers

MULTI HANDSET

- Handset locator
- Conference between the base and the handset
- Up to 4 bases and up to 5 handsets
- Call transfer of external calls (when using several handsets)
- Intercom between handset

PHOTODECT295 (Handset)

- Hearing aid compatible
- Adjustable receiving volume: up to 30dB
- 4 one-touch photo keys:
 - Large photo keys: 3 x 2 cm
- Adjustable speaker phone volume
- Automatic hang up / on hook
- DECT phone
- Memory storage
- 1 battery ni-Mh 2.4V 500mA (included)
- Recharging base (included)
- Standby time: 2 days
- Talk time: 8 hours
- Speakerphone
- Outdoor range: 300m
- Indoor range: 50m

RINGER

- 10 ringtones for the base and 10 ringtones for the handset
- Adjustable ring volume (Mute + 5 positions)
- Visual ring indicator on the base and on the handset
- Ringtone volume:
 - **80dB** on the base
 - **75dB** on the handset

TECHNICAL SPECIFICATIONS

- 1 battery ni-Mh 2.4V 500mA (included)
- Memory storage
- Power supply by AC adapter (supplied)
- Dial/Decimal voice frequency
- Main phone wall mountable
- GAP compliant
- Range:
 - Indoor: up to 50m
 - Open field: up to 300m

CALLER ID * (BASE)

- Name presentation in hook mode (type 1) and conversation mode (type 2)
 - 20 incoming numbers
- Caller ID also for Call waiting
- Indicator call waiting
- Indicator new call



AmpliDect295 AD PhotoDect295

ADDITIONAL HANDSETS

- AmpliDect295 AD
- PhotoDect295

FAMILY PRODUCTS

- AmpliDect295
- AmpliDect295 SOS-PRO
- AmpliDect295 DUO
- AmpliDect295 Photo
- AmpliDect Combi 295

*To use the CID facility it will be necessary to subscribe to your network provider's CID service
Items pictured and details are subject to change at the manufacturer's discretion.